

# 8 colors FLEXO printing press



By ABTECH S.R.L. - ITALY



<b>Reference</b>	F49
1.01 <b>Brand</b>	<b>UTECO</b>
1.02 <b>Model</b>	<b>Onyx 808 GL</b>
1.03 <b>Year</b>	2014 (in production since 2015)
1.04 <b>Colors (No.)</b>	8
1.05 <b>Gearless</b>	Yes
1.06 <b>Printing width (mm)</b>	1.400
1.07 <b>Web width (mm)</b>	1.450
1.08 <b>Printing repeat range (mm)</b>	380 - 800
1.09 <b>Mechanical speed (m/min)</b>	400
1.10 <b>Clichés rollers: type and quantity</b>	Sleeve; No. 96 and No. 2 set of carrier in supply
1.11 <b>Anilox rollers: type and quantity</b>	Sleeve; No. 20 in supply
1.12 <b>Inks</b>	Solvent base and water base
1.13 <b>Doctor blade groups: type and quantity</b>	Closed chamber; No. 8 groups in supply
1.14 <b>Washing system</b>	Yes, automatic
1.15 <b>Type of unwinder</b>	Flying splice turret with shafts 76 and 152 mm
1.16 <b>Max diameter on unwinder (mm)</b>	1.000
1.17 <b>Type of rewinder</b>	Flying splice turret with shafts 76 and 152 mm
1.18 <b>Max diameter on rewinder (mm)</b>	1.000
1.19 <b>Heating system</b>	No. 2 gas burners
1.20 <b>Video-camera</b>	Brand: GRAFIKONTROL - Model: Grafiscan 2200 (3 Chip) with Click&Drag register control
1.21 <b>Materials to be printed</b>	Paper and plastic films for flexible packaging
1.22 <b>More information</b>	8 inks pumps; 8 GAMA - G29 viscometers; 2 web-guiding systems; UTECO Kiss&Go automatic set-up printing pressure system; longitudinal cutting system on rewinder; LEL solvent detection system